



T-REP - Specially developed for cosmetic repairs to most automotive tyre and rubber compounds.

Directions- Clean surface area ensuring it is dry and dust free.
Remove end cap from cartridge, attach our Savemix nozzle and twist in place.
Using our T-REP gun pull plunger fully out and side load the cartridge.
Now apply pressure to the trigger until the desired amount has been dispensed to the repair area. Press the release switch at the back of the gun to prevent any ' over-run '. After 4 mins T-REP WELD is fully cured and ready to sand if required. Now allow left over material to go off in the nozzle for storage.
To reuse simply remove old nozzle and repeat the process.

IMPORTANT: NOT TO BE USED FOR PUNCTURE REPAIRS. PROFFESIONAL USE ONLY.

WWW.T-REPS.CO.UK



DANGER. Harmful if inhaled. Causes serious eye irritation. May cause respiratory irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or

repeated exposure by inhalation (respiratory system). Obtain special instructions before use. Do not breathe vapours or spray. Wear protective gloves / protective clothing and eye protection / face protection. Wear respiratory protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE / doctor if you feel unwell. Contains isocyanates. May produce an allergic reaction. Contains: 4,4'-methylenediphenyl diisocyanate, Diphenylmethanediisocyanate, isomeres and homologues and Methylenediphenyl diisocyanate, modified.